









**Conductos con caño llano.**  
**Desvío limitado**

KWIX	REF.				L/ha → 					
					4 km/h	5 km/h	6 km/h	7 km/h	8 km/h	9 km/h
RLX 80-015 ALX 80-015 VERDE	52006 52009	80°	1,75	0,44	132	106	88	76	66	
			2	0,48	144	115	96	82	72	
			2,5	0,54	162	130	108	93	81	72
			3	0,59	177	142	118	101	89	78
			3,5	0,62	186	150	124	106	93	82
			4	0,68	204	163	136	117	102	90
			5	0,75	225	180	150	129	112	100
RLX 110-02 ALX 110-02 AMARILLO	52007 52010	110°	1,75	0,60	180	144	120	103	90	80
			2	0,65	195	156	130	111	98	86
			2,5	0,72	216	173	144	123	108	96
			3	0,79	237	190	158	135	119	105
			3,5	0,85	255	204	170	146	127	113
			4	0,91	273	218	182	156	137	121
			5	1,01	303	242	202	173	151	134
RLX 110-03 ALX 110-03 AZUL	52008 52011	110°	1,75	0,90	270	216	180	154	135	120
			2	0,97	291	233	194	166	146	129
			2,5	1,08	324	259	216	185	162	144
			3	1,18	354	283	236	202	177	157
			3,5	1,28	384	307	256	219	192	170
			4	1,37	411	329	274	235	206	182
			5	1,53	459	367	306	262	229	204

KWIX	REF.				L/ha → 					
					10 km/h	11 km/h	12 km/h	13 km/h	14 km/h	15 km/h
RLX 80-015 ALX 80-015 VERDE	52006 52009	80°	1,75	0,44						
			2	0,48						
			2,5	0,54	65					
			3	0,59	71					
			3,5	0,62	74	67				
			4	0,68	82	74	68			
			5	0,75	90	81	75	69		
RLX 110-02 ALX 110-02 AMARILLO	52007 52010	110°	1,75	0,60	72	65				
			2	0,65	78	71	65			
			2,5	0,72	86	78	72	66		
			3	0,79	95	86	79	73	67	
			3,5	0,85	102	92	85	78	72	68
			4	0,91	109	99	91	84	78	72
			5	1,01	121	110	101	93	86	80
RLX 110-03 ALX 110-03 AZUL	52008 52011	110°	1,75	0,90	108	98	90	83	77	72
			2	0,97	116	106	97	89	83	77
			2,5	1,08	130	118	108	99	92	86
			3	1,18	142	128	118	109	101	94
			3,5	1,28	154	139	128	118	109	102
			4	1,37	164	149	137	126	117	109
			5	1,53	184	167	153	141	131	122